

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



4

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ :
H04L 12/00

A2

(11) International Publication Number:

WO 98/56140

(43) International Publication Date: 10 December 1998 (10.12.98)

(21) International Application Number: PCT/GB98/01651

(22) International Filing Date: 5 June 1998 (05.06.98)

(30) Priority Data:
97/5022 6 June 1997 (06.06.97) ZA

(71) Applicant (for all designated States except US): SALBU RE-SEARCH AND DEVELOPMENT (PROPRIETARY) LIMITED [ZA/ZA]; Portion 86-87 of Farm Doornkloof, Pretoria 0002 (ZA).

(71) Applicant (for IS only): TOMLINSON, Kerry, John [GB/GB]; 79 Hove Park Road, Hove, East Sussex BN3 6LL (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): LARSEN, Mark, Sievert [ZA/ZA]; 22 Darlington Road, Lynnwood Manor, Pretoria 0081 (ZA). LARSEN, James, David [ZA/ZA]; Portion 86-87 of Farm Doornkloof, Pretoria 0002 (ZA).


(74) Agent: TOMLINSON, Kerry, John; Frank B. Dehn & Co., 179 Queen Victoria Street, London EC4V 4EL (GB).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published

Without international search report and to be republished upon receipt of that report.

(54) Title: METHOD OF OPERATION OF A MULTI-STATION NETWORK



(57) Abstract

The invention provides a method of operating a communication network. The network comprises numerous stations, each of which can transmit and receive data in order to transmit messages from originating stations to destination stations opportunistically via intermediate stations. Each station selects one of a number of possible calling channels to transmit probe signals to other stations. The probe signals contain data identifying the station in question and include details of its connectivity to other stations. Other stations receiving the probe signals respond directly or indirectly, thereby indicating both to the probing station and other stations their availability as destination or intermediate stations. The probing station evaluates the direct or indirect responses to identify other stations with which it can communicate optimally. For example, the stations may monitor the cumulative power required to reach another station, thereby defining a power gradient to the other stations, with stations selecting a route through the network which optimises the power gradient. Thus, data throughput through the network is maximised with minimum interference and contention between stations.

METHOD OF OPERATION OF A MULTI-STATION NETWORK

Patent number: WO9856140
Publication date: 1998-12-10
Inventor: LARSEN MARK SIEVERT (ZA); LARSEN JAMES DAVID (ZA)
Applicant: TOMLINSON KERRY JOHN (GB); LARSEN MARK SIEVERT (ZA); SALBU RES AND DEV PTY LTD (ZA); LARSEN JAMES DAVID (ZA)
Classification:
- international: H04L12/00
- european: H04L12/56C1; H04L12/56B
Application number: WO1998GB01651 19980605
Priority number(s): ZA19970005022 19970606

Also published

WO9856
EP09852
EP09852
AU76059

Cited document

US54855
US48645
US54307
WO8905

Abstract of WO9856140

The invention provides a method of operating a communication network. The network comprises numerous stations, each of which can transmit and receive data in order to transmit messages from originating stations to destination stations opportunistically via intermediate stations. Each station selects one of a number of possible calling channels to transmit probe signals to other stations. The probe signals contain data identifying the station in question and include details of its connectivity to other stations. Other stations receiving the probe signals respond directly or indirectly, thereby indicating both to the probing station and other stations their availability as destination or intermediate stations. The probing station evaluates the direct or indirect responses to identify other stations with which it can communicate optimally. For example, the stations may monitor the cumulative power required to reach another station, thereby defining a power gradient to the other stations, with stations selecting a route through the network which optimises the power gradient. Thus, data throughput through the network is maximised with minimum interference and contention between stations.

